

THD-65+65

- ◆ 副台採固定式，適用於大型PET吹膜機。
- ◆ The secondary engine is fixed style, it applies to large PET Inflation Machine.



- ▲ 捲取機：單收台、雙收台2種
Winder : Single & Double Two Type

高密度塑膠高速吹袋機

HDPE High Speed Plastic Inflation Machine

Specification

Model No.	型號	THD-65+65
Material applicable	適用原料	High density polyethylene / 高密度聚乙烯
Layflat width	產品寬度	500-1300 mm
Thickness of film	產品厚度	0.0125-0.03 mm
Extrusion capacity	押出量	50-200 kg/hr
Extruder	押出機	
Screw dia.; L/D	螺桿直徑/長比	65 mm ϕ; 28:1
Screw speed	螺桿轉數	20-120 rpm
Drive motor	傳動馬達	40 HP Inverter
Heating capacity	電熱量	48 kws
Screw material	螺桿材質	SCM-4 with High frequency treatment & Hard chrome plating
Cylinder material	塑膠筒材質	SCM-4 with Harden & Nitrided treatment
Gear material	齒輪材質	S-45C with High frequency treatmen
Auto-thermo controller	自動溫度控制器	12 sets
Extrusion die	押出模頭	150/180
Control	控制箱	
Type	型式	Separate & Independent Type / 分開獨立式
Take-up unit	引取機	
Type	型式	Moving upward & Downward Type / 上下可移動式
Drive motor	引取馬達	2 HP A.C.
Height of tower	引取塔高	6000 mm
Width of roller	引取輪寬	1500 mm
Take-up speed	引取速度	80 m/min max
Drive motor of Elevator	昇降器傳動馬達	1/2 HP
Max. distance of elevating	昇降器最大距離	650 mm
Air blower	鼓風機	7.5 HP
Air cooling ring	冷卻風環	1 unit
Steady plate	安定板	1 unit
Winder	捲膜機	
Type	型式	Surface Friction Type / 表面磨擦式
Drive motor	傳動馬達	2 HP torque motor
Max. dia of woung up roll	最大捲起直徑	800 mm max
Effective film width	有效捲膜寬度	1400 mm
Wind-up speed	捲起速度	80 m/min max
Weight of machine	機械重量	4200 kg
Dimension (LxWxH)	機械長寬高	3.8 X 2.5 X 3.8
Measurement (Approx.)	裝箱才數 (約)	40 R/cu.m

機械規格局部修改不另行通知貴戶
Specification is subject to change without notification of modification. Alternative design of combined application for HDPE/LDPE & LLDPE is subject to negotiation.

※旋轉模頭為選擇配備
※Charged Optional : Rotary Die Set